

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes PP Varnish Extra Comp. B (cure)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category
 - PROC7 Industrial spraying
 - PROC11 Non industrial spraying
 - PROC10 Roller application or brushing
- Environmental release category
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
 - ERC5 Use at industrial site leading to inclusion into/onto article
- Article category AC11 Wood articles
- Application of the substance / the mixture
See our technical datasheet for application of this product.
Curing component of a high build two-component varnish
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31-(0)297-360366
email: r&d@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number:
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: rend@epifanes.nl
Office hours: weekdays from 08:00 to 17:00.
The National Poisons Information Service; dial 111
Solely intended to inform professionals in acute poisoning!

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 1)

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Additional information: For professional use only.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02



GHS07



GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Xylene

aromatic polyisocyanate

m-tolyldiene diisocyanate

Ethylbenzene

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 2)

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Additional information:

Contains isocyanates. May produce an allergic reaction.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 53317-61-6 Reg.nr.: niet van toepassing	aromatic polyisocyanate ! Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics. (Note-P) Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	≥10-<25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	2.5-10%

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 3)

<p>CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35</p>	<p>Ethylbenzene ----- ⚠ Flam. Liq. 2, H225 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335</p>	<p>≤2.5%</p>
<p>CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34</p>	<p>m-tolylidene diisocyanate ----- ⚠ Acute Tox. 2, H330 ⚠ Resp. Sens. 1, H334; Carc. 2, H351 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 Aquatic Chronic 3, H412 EUH204 Specific concentration limit: Resp.Sens. 1; H334: C ≥ 0.1 %</p>	<p>≥0.1-<0.3%</p>

· Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

GB

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 4)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 5)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

100-41-4 Ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

26471-62-5 m-tolyldiene diisocyanate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

100-41-4 Ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

26471-62-5 m-tolyldiene diisocyanate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

· Regulatory information WEL: EH40/2020

· DNEL (Derived No Effect Level) voor professionals

1330-20-7 Xylene

Oral	Long-term - systemic effects.	1.6 mg/kg bw/day (General population)
Inhalative	Long-term - local effects.	77 mg/m ³ (Employees)
	Acute - systemic effects.	174 mg/m ³ (General population)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 6)

	Long-term - systemic effects.	14.8 mg/m ³ (General population)
64742-95-6 Hydrocarbons, C9, aromatics. (Note-P)		
Oral	Long-term - systemic effects.	11 mg/kg/day (General population)
Dermal	Long-term - systemic effects.	25 mg/kg/day (Industry)
	Long-term systemic effects.	11 mg//kg/day (General population)
Inhalative	Long-term - systemic effects.	32 mg/m ³ (General population)
	Long-term - systemic effects.	150 mg/m ³ (Industry)
	Long-term exposure (8 hours TWA) 19 ppm	100 mg/m ³ (Occupational exposure limits)
108-65-6 2-methoxy-1-methylethyl acetate		
Dermal	Long-term systemic effects.	796 mg//kg/day (Employees)
Inhalative	Short term - local effects.	550 mg/m ³ (Employees)
	Long-term - systemic effects.	275 mg/m ³ (Employees)
100-41-4 Ethylbenzene		
Dermal	Long-term - systemic effects.	180 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	77 mg/m ³ (Employees)
	Short-term systemic effects.	293 mg/m ³ (Employees)
26471-62-5 m-tolyldiene diisocyanate		
Inhalative	Long-term - local effects.	0.035 mg/m ³ (Employees)
	Long-term - systemic effects.	0.035 mg/m ³ (Employees)
· DNEL (Derived No Effect Level) for general audience		
1330-20-7 Xylene		
Oral	Acute - systemic effects	289 mg/kg (Employees)
Dermal	Long-term - systemic effects.	180 mg/kg bw/day (Employees)
Inhalative	Long-term - systemic effects.	77 mg/m ³ (Employees)
	Short-term - systemic effects.	289 mg/kg (Employees)
	Short-term - local effects.	174 mg/m ³ (General population)
	Long term - systemic effects.	108 mg/kg bw/day (General population)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	Long-term systemic effects.	36 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	320 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	33 mg/m ³ (General population)
100-41-4 Ethylbenzene		
Oral	Long-term systemic effects.	1.6 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	15 mg/m ³ (General population)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 7)

· PNECs	
1330-20-7 Xylene	
Sewage treatment plant	6.58 mg/l (Sewage treatment plant)
Aquatic compartment.	0.327 mg/l (Freshwater)
Aquatic compartment.	0.327 mg/l (Seawater)
Aquatic compartment - water, intermittent releases	0.327 mg/L (Freshwater)
Soil	12.46 mg/kg (Seawater)
	12.46 mg/kg (Freshwater)
Soil	2.31 mg/kg (soil)
108-65-6 2-methoxy-1-methylethyl acetate	
Sewage treatment plant	100 mg/l (Sewage treatment plant)
Aquatic compartment.	0.635 mg/l (Freshwater)
Aquatic compartment.	0.0635 mg/l (Seawater)
Soil	3.29 mg/kg (Freshwater)
Intermittent	6.35 mg/l (Intermittent)
Soil	0.29 mg/kg (soil)
Sediment	0.329 mg/kg (Seawater)
100-41-4 Ethylbenzene	
Sewage treatment plant	9.6 mg/l (Sewage treatment plant)
Aquatic compartment.	0.1 mg/l (Freshwater)
Aquatic compartment - water, intermittent releases	0.01 mg/L (Seawater)
Soil	13.7 mg/kg (Freshwater)
Intermittent	0.1 mg/l (Intermittent)
Soil	2.68 mg/kg (soil)
Sediment	1.37 mg/kg (Seawater)
26471-62-5 m-tolyldiene diisocyanate	
Aquatic compartment.	0.013 mg/l (Freshwater)
Aquatic compartment.	0.001 mg/l (Seawater)
STP	1 mg/l (Segmentation, Targeting and Positioning)
Soil	1 mg/kg (soil)

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 8)

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- Respiratory protection:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter AX
In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Butyl rubber, BR
- Eye/face protection



Tightly sealed goggles

GB

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 9)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Physical state Fluid
- Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range 36 °C (1330-20-7 Xylene)
- Flammability Not applicable.
- Lower and upper explosion limit
- Lower: 1.5 Vol %
- Upper: 11.5 Vol %
- Flash point: >23 °C (1330-20-7 Xylene)
- Auto-ignition temperature: Product is not selfigniting.
- Decomposition temperature: Not determined.
- pH Not determined.
- Viscosity:
- Kinematic viscosity at 20 °C 40 s (ISO 6 mm)
- Dynamic: Not determined.
- Solubility
- water: Fully miscible.
- Partition coefficient n-octanol/water (log value) Not determined.
- Vapour pressure: Not determined.
- Density and/or relative density
- Density at 20 °C: 1.03698 g/cm³
- Relative density Not determined.
- Vapour density Not determined.

- 9.2 Other information
- Appearance:
- Form: Fluid
- Important information on protection of health and environment, and on safety.
- Ignition temperature: 315 °C (108-65-6 2-methoxy-1-methylethyl acetate)
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Solvent content:
- Organic solvents: 60.3 %
- VOC content: 60.26 %
- VOC content: 624.8 g/l / 5.21 lb/gal
- Solids content: 39.7 %
- Change in condition
- Evaporation rate Not determined.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 10)

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Flammable liquid and vapour.
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Harmful if inhaled.

- LD/LC50 values relevant for classification:

1330-20-7 Xylene

Dermal	Short-term exposure (15 minutes): 100 ppm	442 mg/m ³ (Occupational exposure limits)
	Long-term exposure (8 hours TWA): 50 ppm	221 mg/m ³ (Occupational exposure limits)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg bw (rat)
Dermal	Long-term exposure (8 hours TWA): 50 ppm	550 mg/m ³ (Occupational exposure limits)

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 11)

Inhalative	LC50/4 h	35.7 mg/l (rat)
100-41-4 Ethylbenzene		
Oral	LD50	3,500 mg/kg bw (rat)
Dermal	LD50	17,800 mg/kg bw (rabbit)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- STOT-single exposure
May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure
May cause damage to the hearing organs through prolonged or repeated exposure.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

108-65-6 2-methoxy-1-methylethyl acetate

EC50 408-500 mg/l (daphnia magna) (48 uur/hour)

IC 50 >1,000 mg/l (Algae, Growth inhibition test) (72 uur/hour)

LC50 100-180 mg/l (Fish Acute Toxicity Study) (96 uur/hour)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
· PBT: Not applicable.
· vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
· Remark: Harmful to fish
- Additional ecological information:
· General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

GB

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022



Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 12)

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents:
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | |
|---|-----------------------------|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name | |
| · ADR | 1263 PAINT |
| · IMDG, IATA | PAINT |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 3 (F1) Flammable liquids. |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Hazard identification number (Kemler code): | 30 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | A |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 13)

· Transport/Additional information:

· ADR

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging:
30 ml

Maximum net quantity per outer packaging:
1000 ml

· Transport category

3

· Tunnel restriction code

D/E

· Remarks:

> 450 l: 3 F1, III

· IMDG

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging:
30 ml

Maximum net quantity per outer packaging:
1000 ml

· Remarks:

> 30 l: 3, III

· UN "Model Regulation":

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t
- National regulations:
- Technical instructions (air):

Class	Share in %
I	≤0.5
NK	50-100

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 15)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes PP Varnish Extra Comp. B (cure)

(Contd. of page 14)

• Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH204 Contains isocyanates. May produce an allergic reaction.

• Department issuing SDS: Research & Development.

• Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl

• Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids - Category 2
- Flam. Liq. 3: Flammable liquids - Category 3
- Acute Tox. 4: Acute toxicity - Category 4
- Acute Tox. 2: Acute toxicity - Category 2
- Skin Irrit. 2: Skin corrosion/irritation - Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
- Resp. Sens. 1: Respiratory sensitisation - Category 1
- Skin Sens. 1: Skin sensitisation - Category 1
- Carc. 2: Carcinogenicity - Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2
- Asp. Tox. 1: Aspiration hazard - Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

• * Data compared to the previous version altered.