

MOTIP Metallic Paint

Technical Information



Fast-drying acrylic paint for treated and untreated surfaces including wood, metal, aluminium, stone and various types of plastic. It offers excellent adhesion and is resistant to scratches and the weather. For best results, first apply a base layer of MOTIP White Primer.

Ord.-no: 04043, 04044, 04045, 04046, 04047, 04048, 04049, 04050

Quality & properties

Fast drying
Wear resistant
Resistant to weather influences
Excellent coverage

Physical & chemical data

Base: Nitrocombi resin

Colourname:

- green
- blue
- red
- silver
- gold
- brown
- black
- violet

Degree of gloss: gloss GU

Efficiency: 400 ML – 1.25 - 1.75 m²

Dry to touch: 10 - 20 min

Dust dry: 5 - 10 min

Completely dry: 120 min

Overcoatable: 120 min

Surfaces: Wood, metal, glass, stone and various types of plastic.

Minimum Working Temperature: 10 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Temperature Resistance: 110 °C

Storage stability: 10 y

Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment: The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. In order to achieve the best metallic effect, apply a layer of white MOTIP primer. When treating surfaces of plastic, first apply a layer of plastic primer before applying the MOTIP white primer. After drying, sand the base layer (grain 600).

Treatment: The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C.

Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Recommendation: The metallic effect is increased by using a first layer of MOTIP Wheel Spray Silver and by applying a finishing layer of MOTIP acrylic clear varnish.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.