according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 2014-2 RESIN

Unique Formula Identifier

(UFI)

: 97GS-W06K-200K-C9WU

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Epoxy constituents

Substance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV

Address : Grijpenlaan 18

3300 Tienen Belgium

Telephone : +41 61 299 20 41 Telefax : +41 61 299 20 40

E-mail address of person

responsible for the SDS

: Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone

Emergency telephone : Berlin: 0049 30 19 24 0 & 0049 30 30 68 6 7 11

Bonn: 0049 228 19 27 0 & 0049 228 28 7 3 32 11

Erfurt: 0049 361 73 07 30 Freiburg: 0049 761 16 24 0

Göttingen: 0049 51 19 24 0 & 0049 551 38 31 80

Homburg: 0049 6841 19 24 0

Mainz: 0049 6131 19 24 0 & 0049 6131 23 24 66

München: 0049 89 19 24 0 Nürnberg: 0049 911 39 8 2 45 1 EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090 India: + 91 22 42 87 5333

Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Serious eye damage, Category 1 H318: Causes serious eye damage.
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Reproductive toxicity, Category 1B H360F: May damage fertility.

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects.

Category 2

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

Prevention:

Precautionary Statements : P201 Obtain special instructions before use.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection/ hearing protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/

doctor.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P391 Collect spillage.

Hazardous ingredients which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane

1,4-bis(2,3 epoxypropoxy)butane

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concent ration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxir ane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 >= 5 % Eye Irrit. 2; H319 >= 5 %	>= 30 - < 50
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]bis(oxir ane) and 2,2'-[methylenebis(4,1- phenyleneoxymethylene)]bis(oxir ane) and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}meth yl)oxirane	- - 01-2119454392-40	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 10 - < 20
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7 01-2119494060-45	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Repr. 1B; H360F Acute toxicity estimate Acute dermal toxicity: 1 100 mg/kg	>=1-<
Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate	Not Assigned - 01-2120065788-39	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Repr. 2; H361f STOT RE 2; H373 (Central nervous system, male	>= 1 - < 2,5

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

	reproductive organs) Aquatic Chronic 2; H411	
	M-Factor (Chronic aquatic toxicity): 1	

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage.

May damage fertility.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Carbon oxides
Phenolics

Sulfur oxides

5.3 Advice for firefighters

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

and/or dermatitis and sensitization of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label

precautions. Keep in properly labeled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this

SDS.

Storage class (TRGS 510) : 6.1C

Recommended storage

temperature

2 - 40 °C

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Further information on

storage stability

: Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
barium sulfate	7727-43-7	AGW (Inhalable	10 mg/m3	DE TRGS
		fraction)	J	900
	Peak-limit cate	egory: 2;(II)		
			compliance with the OEL ar	nd biological
	tolerance valu		of harming the unborn child	
		AGW (Alveolate	1,25 mg/m3	DE TRGS
		fraction)		900
	Peak-limit cate	egory: 2;(II)		
	Further inform	ation: When there is	compliance with the OEL ar	nd biological
	tolerance valu	es, there is no risk o	f harming the unborn child	
		BM (Alveolar	0,5 mg/m3	DE TRGS
		dust fraction)		527
		MAK (measured	0,3 mg/m3	DE DFG MAK
		as the alveolate		
		fraction)		
	Peak-limit category: 8; II			
	Further information: Substances that cause cancer in humans or animals or			
	that are considered to be carcinogenic for humans and for which a MAK value			
	can be derived., Damage to the embryo or foetus is unlikely when the MAK			
	value or the BAT value is observed			
		MAK (inhalable	4 mg/m3	DE DFG MAK
		fraction)		
	Peak-limit category: 8; II			
	Further information: Substances that cause cancer in humans or animals or			
	that are considered to be carcinogenic for humans and for which a MAK value			
	can be derived., Damage to the embryo or foetus is unlikely when the MAK			
	value or the BAT value is observed			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

3				
Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethyle ne)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4,93 mg/m3
	Workers	Dermal	Long-term systemic	0,75 mg/kg

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

	I		effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,5 mg/kg bw/day
1,4-bis(2,3 epoxypropoxy)butane	Workers	Inhalation	Long-term systemic effects	4,7 mg/m3
	Workers	Dermal	Long-term systemic effects	6,66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,16 mg/m3
	Consumers	Dermal	Long-term systemic effects	3,33 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,33 mg/kg bw/day
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethyle ne)]bis(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethyle ne)]bis(oxirane) and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phe noxy}methyl)oxirane	Workers	Dermal	Acute local effects	0,0083 mg/cm2
	Workers	Dermal	Long-term systemic effects	104,15 mg/kg
	Workers	Inhalation	Long-term systemic effects	29,39 mg/m3
	Consumers	Dermal	Long-term systemic effects	62,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	8,7 mg/m3
	Consumers	Oral	Long-term systemic effects	6,25 mg/kg bw/day
Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4- tricarboxylate	Workers	Inhalation	Long-term systemic effects	0,025 mg/m3
	Workers	Dermal	Long-term systemic effects	0,05 mg/kg bw/day
barium sulfate	Workers	Inhalation	Long-term systemic effects	10 mg/m3
	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumer use	Inhalation	Long-term systemic effects	10 mg/m3
	Consumer use	Oral	Long-term systemic	13000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

effects

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxira	Fresh water	0,006 mg/l
ne		
	Sea water	0,001 mg/l
	Fresh water sediment	0,341 mg/kg dry
		weight (d.w.)
	Sea sediment	0,034 mg/kg dry
		weight (d.w.)
	Soil	0,065 mg/kg dry
	Covers treatment plant	weight (d.w.)
	Sewage treatment plant Secondary Poisoning	10 mg/l 11 mg/kg
1,4-bis(2,3 epoxypropoxy)butane	Fresh water	0,024 mg/l
1,4-bis(2,3 epoxypropoxy)butarie	Remarks:Assessment Factors	0,024 mg/i
	Sea water	0,002 mg/l
	Remarks:Assessment Factors	0,002 mg/i
	Sewage treatment plant	100 mg/l
	Remarks: Assessment Factors	· · · · · · · · · · · · · · · · · · ·
	Fresh water sediment	0,084 mg/kg dry
		weight (d.w.)
	Remarks:Equilibrium method	
	Sea sediment	0,008 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	i u sig. i (u i i i)
	Soil	0,003 mg/kg dry
		weight (d.w.)
	Remarks:Equilibrium method	
	Oral	0,028 mg/kg
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]bis(oxir ane) and 2,2'-[methylenebis(4,1- phenyleneoxymethylene)]bis(oxir ane) and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}methy l)oxirane	Fresh water	0,003 mg/l
	Remarks: Assessment Factors	
	Sea water	0 mg/l
	Remarks: Assessment Factors	0.0054/
	Intermittent use/release Remarks:Assessment Factors	0,0254 mg/l
	Fresh water sediment	0,294 mg/kg dry
	i resii water sediment	weight (d.w.)
	Remarks:Equilibrium method	T Worgill (d.W.)
	Sea sediment	0,0294 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	moigni (d.m.)
	Soil	0,237 mg/kg dry
	3011	weight (d.w.)

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

	Sewage treatment plant	10 mg/l	
	Remarks: Assessment Factors		
Siloxanes and silicones, di-Me, reaction products with silica	Fresh water sediment	> 100 mg/kg	
	Remarks: Assessment Factors		
	Soil	23 mg/kg	
	Remarks: Assessment Factors	·	
Reaction mass of bis(2,3- epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene- 1,2,4-tricarboxylate	Fresh water	0,003 mg/l	
·	Remarks: Assessment Factors	•	
	Sea water	0 mg/l	
	Remarks: Assessment Factors		
	Freshwater - intermittent	0,027 mg/l	
	Remarks: Assessment Factors		
	Sewage treatment plant	32 mg/l	
	Remarks: Assessment Factors		
	Fresh water sediment	0,044 mg/kg dry weight (d.w.)	
	Remarks:Equilibrium method	·	
	Sea sediment	0,004 mg/kg dry weight (d.w.)	
	Remarks:Equilibrium method		
	Soil	0,007 mg/kg dry weight (d.w.)	
	Remarks:Equilibrium method		
barium sulfate	Fresh water	115 µg/l	
	Sewage treatment plant	62,2 mg/l	
	Remarks: Assessment Factors		
	Fresh water sediment	600,4 mg/kg	
	Remarks:Assessment Factors		
	Soil	207,7 mg/kg	
	Remarks: Assessment Factors		

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : butyl-rubber

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Remarks : Gloves should be discarded and replaced if there is any

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines

Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapor type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Form : No data is available on the product itself.

Color : beige

Odor : slight

Odor Threshold : No data is available on the product itself.

Melting point/freezing point : No data available

Boiling point/boiling range : > 200 °C

Flammability : No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Flash point : $> 100 \, ^{\circ}\text{C}$

Method: closed cup

Autoignition temperature : does not ignite

Decomposition temperature : > 200 °C

pH : ca. 7 (20 °C)

Concentration: 500 g/l

Viscosity

Viscosity, dynamic : 92 800 mPa.s (25 °C) Method: Other guidelines

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Solubility(ies)

Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Vapor pressure : < 1,33 hPa (20 °C)

Density : 1,6 g/cm3 (25 °C)

Relative density : No data is available on the product itself.

Relative vapor density : No data is available on the product itself.

Particle characteristics : No data is available on the product itself.

9.2 Other information

No data is available on the product itself.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2 000 mg/kg

Method: Calculation method

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2 000 mg/kg

Method: Calculation method

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral

toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Acute oral toxicity : LD50 (Rat, male and female): > 5 000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

1,4-bis(2,3 epoxypropoxy)butane:

Acute oral toxicity : LD50 (Rat, male and female): 1 163 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity : LC50 (Rat): > 2,068 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Test atmosphere: dust/mist Method: Expert judgment

Assessment: The component/mixture is moderately toxic after short term inhalation., The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute dermal toxicity : Acute toxicity estimate: 1 100 mg/kg

Method: Converted acute toxicity point estimate

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Assessment: The component/mixture is moderately toxic after

single contact with skin.

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Acute oral toxicity : LD50 (Rat, female): > 300 - < 2 000 mg/kg

Method: OECD Test Guideline 423

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit Exposure time : 4 h

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:
Species : Rabbit

Method : OECD Test Guideline 404

Result : Irritating to skin.

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

GLP : yes

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Species : Rabbit

Assessment : Irritating to skin.

Method : No information available.

Result : Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Result : Irritating to eyes.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rabbit

Assessment : Risk of serious damage to eyes.

Method : OECD Test Guideline 405

GLP : yes

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Species : Rabbit Assessment : Irritant

Method : OECD Test Guideline 405
Result : Normally reversible injuries

Species : Rabbit Assessment : Corrosive

Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : The product is a skin sensitiser, sub-category 1B.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : The product is a skin sensitiser, sub-category 1A.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

1,4-bis(2,3 epoxypropoxy)butane:

Exposure routes : Skin Species : Guinea pig

Method : OECD Test Guideline 406

Result : May cause sensitisation by skin contact.

GLP : yes

Assessment : Harmful if inhaled.

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Exposure routes : Skin Species : Guinea pig

Method : OECD Test Guideline 406

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

Test Type: reverse mutation assay Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse

mutation assay) Result: negative

Genotoxicity in vivo : Test Type: in vivo assay

Species: Mouse (male)
Cell type: Germ
Application Route: Oral
Dose: 3333, 10000 mg/kg

Result: negative

Test Type: gene mutation test

Species: Rat (male) Cell type: Somatic Application Route: Oral

Dose: 50,250,500,1000 mg/kg bw/day Method: OECD Test Guideline 488

Result: negative

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Genotoxicity in vivo : Cell type: Somatic

Application Route: Oral Exposure time: 48 h Dose: 2000 mg/kg

Method: OECD Test Guideline 474

Result: negative

Cell type: Somatic Application Route: Oral Dose: 2000 mg/kg

Method: OECD Test Guideline 486

Result: negative

1,4-bis(2,3 epoxypropoxy)butane:

Genotoxicity in vitro : Test Type: reverse mutation assay

Concentration: 10 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive GLP: yes

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster lung cells

Concentration: 1 - 100 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive GLP: yes

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

GLP: no

Remarks: Not classified due to data which are conclusive

although insufficient for classification.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse (male) Cell type: Somatic Application Route: Oral Exposure time: 4 d Dose: 187.5 - 750 mg/kg

Method: OECD Test Guideline 474

Result: negative

GLP: yes

Test Type: unscheduled DNA synthesis assay

Species: Rat

Cell type: Liver cells Application Route: Oral

Method: OECD Test Guideline 486

Result: negative

Test Type: gene mutation test

Species: Rat (male) Cell type: Somatic Application Route: Oral

Dose: 0, 62.5, 125 and 250 mg/kg Method: OECD Test Guideline 488

Result: negative

Germ cell mutagenicity-

Assessment

Weight of evidence does not support classification as a germ

cell mutagen., Animal testing did not show any mutagenic

effects.

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive GLP: yes

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive GLP: yes

Test Type: gene mutation test

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive GLP: yes

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro

Species: Mouse (male)

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Cell type: Germ Application Route: Oral Exposure time: 5 d Dose: 0 - 720 mg/kg

Method: OECD Test Guideline 483

Result: negative

Test Type: Chromosome aberration test in vitro

Species: Mouse (male) Cell type: Germ Application Route: Oral Exposure time: 5 d Dose: 0 - 360 mg/kg

Method: OECD Test Guideline 483

Result: negative

Test Type: Micronucleus test Species: Rat (male and female)

Application Route: Intraperitoneal injection

Dose: 2500 mg/kg

Method: OECD Test Guideline 474

Result: negative

Test Type: Micronucleus test Species: Rat (male and female)

Application Route: Intraperitoneal injection

Dose: 1500 mg/kg

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male Application Route : Oral

Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week NOAEL : 15 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Mouse, male
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0, 0.1, 10, 100 mg/kg bw/day

Frequency of Treatment : 3 days/week

NOEL : 0,1 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0.1, 100, 1000 mg/kg bw/day

Frequency of Treatment : 5 days/week

NOEL : 100 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Species : Rat, female

Application Route : Oral

Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week

NOAEL : 100 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Rat, females

Application Route : Oral

Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week
NOEL : 2 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Reproductive toxicity

May damage fertility.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 milligram per kilogram

Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily

General Toxicity Parent: NOEL: 540 mg/kg body weight

General Toxicity F1: NOEL: 750 mg/kg body weight Symptoms: No adverse effects Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Effects on fetal development : Species: Rabbit, female

Application Route: Dermal

Dose: 0, 30, 100 or 300 milligram per kilogram

Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 30 mg/kg body weight

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: Other guidelines Result: No teratogenic effects

Test Type: Pre-natal Species: Rabbit, female Application Route: Oral

Dose: 0, 20, 60 or 180 milligram per kilogram

Duration of Single Treatment: 13 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 60 mg/kg body weight Developmental Toxicity: NOAEL: 180 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 0, 60, 180 and 540 milligram per kilogram

Duration of Single Treatment: 10 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 180 mg/kg body weight Developmental Toxicity: NOAEL: > 540 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 mg/kg/ Duration of Single Treatment: 238 d General Toxicity Parent: NOEL: 750

General Toxicity F1: NOEL: 750 mg/kg body weight General Toxicity F2: NOAEL: 750 mg/kg body weight

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

1,4-bis(2,3 epoxypropoxy)butane:

Effects on fertility : Test Type: reproductive and developmental toxicity study

Species: Rat, male and female

Application Route: Oral

Dose: 0/50/200/500 mg/kg bw/day Duration of Single Treatment: 43 d

General Toxicity Parent: LOEL: 500 mg/kg body weight General Toxicity F1: LOAEL: 500 mg/kg body weight

Target Organs: Gastrointestinal tract Method: OECD Test Guideline 421

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

GLP: yes

Test Type: Extended one-generation reproduction toxicity

study

Species: Rat, male and female

Application Route: Oral

Dose: 0/10/55/300 mg/kg bw/day

General Toxicity Parent: NOAEL: 55 mg/kg body weight General Toxicity F1: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 443

GLP: yes

Effects on fetal development : Test Type: Pre-natal

Species: Rat, female Application Route: Oral

Dose: 0/30/100/300 mg/kg bw/day Duration of Single Treatment: 17 d

General Toxicity Maternal: NOAEL: 300 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Test Type: reproductive and developmental toxicity study

Species: Rat, male and female

Application Route: Oral

Dose: 0/33/110/300 mg/kg bw/day Duration of Single Treatment: 18 d

General Toxicity Maternal: NOAEL: 110 mg/kg body weight Embryo-fetal toxicity.: NOAEL: 300 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Test Type: Pre-natal Species: Rabbit Application Route: Oral

Dose: 0/125/250/500 mg/kg bw/day

General Toxicity Maternal: NOAEL: 250 mg/kg body weight Embryo-fetal toxicity.: NOAEL: 250 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Reproductive toxicity -

Assessment

Clear evidence of adverse effects on sexual function and

fertility, based on animal experiments.

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Effects on fertility : Test Type: reproductive and developmental toxicity study

Species: Rat, male and female

Application Route: Oral

Dose: 0,3,15,30 milligram per kilogram Frequency of Treatment: 7 days/week

General Toxicity Parent: NOAEC: 3 mg/kg body weight

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

General Toxicity F1: NOAEC: 30 mg/kg body weight

Fertility: LOAEL: 15 mg/kg body weight

Test Type: reproductive and developmental toxicity study

Species: Rat, male and female

Application Route: Oral

Dose: 0,2.5,6,15 milligram per kilogram Frequency of Treatment: 7 days/week

General Toxicity Parent: NOAEC: 15 mg/kg body weight General Toxicity F1: NOAEC: 15 mg/kg body weight

Fertility: NOAEL: 15 mg/kg body weight Method: OECD Test Guideline 443

GLP: yes

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat, females Strain: Sprague-Dawley Application Route: Oral

General Toxicity Maternal: NOEL: 60 mg/kg body weight Developmental Toxicity: NOEL: 60 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Reproductive toxicity -

Assessment

Some evidence of adverse effects on sexual function and

fertility, based on animal experiments., Suspected of

damaging fertility.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Components:

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Exposure routes : Ingestion

Target Organs : Central nervous system, male reproductive organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male and female

NOAEL : 50 mg/kg
Application Route : oral (gavage)
Exposure time : 14 Weeks

Number of exposures : 7 d

Dose : 0, 50, 250, 1000 mg/kg/day Method : OECD Test Guideline 408

Species : Rat, male and female

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

NOAEL : >= 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 5 d

Dose : 0, 10, 100, 1000 mg/kg/day Method : OECD Test Guideline 411

Species: Mouse, maleNOAEL: 100 mg/kgApplication Route: Skin contactExposure time: 13 Weeks

Number of exposures : 3 d

Dose : 0, 1, 10, 100 mg/kg/day
Method : OECD Test Guideline 411

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Species : Rat, male and female

NOAEL : 250 mg/kg Application Route : Ingestion Exposure time : 13 Weeks

Number of exposures : 7 d

Method : Subchronic toxicity

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rat, male and female

NOAEL : 200 mg/kg Application Route : Oral Exposure time : 28 d Number of exposures : daily

Dose : 25, 100, 200, 400 mg/kg

Method : Subacute toxicity

Species : Rat, male and female

NOAEL : 263 mg/kg
Application Route : Oral
Exposure time : 90 h
Number of exposures : daily

Dose : 0,30,100,300 mg/kg bw/day Method : OECD Test Guideline 408

GLP : yes

Remarks : Information given is based on data obtained from similar

substances.

Repeated dose toxicity - : Harmful if inhaled.

Assessment

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Species : Rat, male and female

NOEL : 75 mg/kg NOAEL : 75 mg/kg Application Route : Oral

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Exposure time : 28 d

Method : OECD Test Guideline 407

Target Organs : Central nervous system, male reproductive organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 : 11 mg/l Exposure time: 72 h

Test Type: static test

Test substance: Fresh water Method: EPA-660/3-75-009

NOEC: 4,2 mg/l Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Exposure time: 3 h
Test Type: static test

Test substance: Fresh water

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 0,3 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Toxicity to fish : LC50 (Fish): 2,54 mg/l

Exposure time: 96 h

Test substance: Fresh water Method: Calculation method

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 2,55 mg/l

Exposure time: 48 h

Method: Calculation method

Toxicity to algae/aquatic

plants

: EC50 (Selenastrum capricornutum (green algae)): > 1,8 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: no

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water

GLP: no

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 0,3 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test Analytical monitoring: no Test substance: Fresh water Method: OECD Test Guideline 211

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

1,4-bis(2,3 epoxypropoxy)butane:

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l

End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 203

GLP: no

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 75 mg/l

End point: Immobilization Exposure time: 24 h Test Type: static test Analytical monitoring: no Test substance: Fresh water Method: OECD Test Guideline 202

GLP: no

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 160

mg/

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

NOELR (Pseudokirchneriella subcapitata (green algae)): 40

mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 209

GLP: no

Toxicity to fish (Chronic

toxicity)

NOEC: > 3,2 mg/l Exposure time: 35 d

Species: Danio rerio (zebra fish) Test Type: flow-through test Method: OECD Test Guideline 210

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC: 15 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

GLP: yes

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 8.8 mg/l

End point: mortality Exposure time: 96 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 81 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): > 2,72 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 0,368 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1 000 mg/l

Exposure time: 3 h
Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 209

M-Factor (Chronic aquatic

toxicity)

1

:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge, non-adapted

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)

pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)

pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)

pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Concentration: 3 mg/l Result: Not biodegradable Biodegradation: ca. 0 % Exposure time: 28 d

Method: Directive 67/548/EEC Annex V, C.4.E.

1,4-bis(2,3 epoxypropoxy)butane:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 43 % Exposure time: 28 d

Method: OECD Test Guideline 301F

GLP: yes

Test Type: aerobic

Inoculum: Sewage (STP effluent)

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 38 %

Related to: Dissolved organic carbon (DOC)

Exposure time: 28 d

Method: OECD Test Guideline 301E

GLP: no

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Result: Not readily biodegradable.

Biodegradation: 52,4 % Exposure time: 28 d

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

Method: OECD Test Guideline 301F

GLP: yes

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31

Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 3,242 (25 °C)

octanol/water pH: 7,1

Method: OECD Test Guideline 117

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 150 Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 2,7 - 3,6

octanol/water Method: OECD Test Guideline 117

GLP: yes

1,4-bis(2,3 epoxypropoxy)butane:

Partition coefficient: n- : log Pow: -0,269 (25 °C)

octanol/water pH: 6,7

Method: OECD Test Guideline 117

GLP: ves

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-

1,2,4-tricarboxylate:

Partition coefficient: n- : log Pow: 0,65 (20 °C)

octanol/water

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among : Koc: 445

environmental compartments

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:
Distribution among : Koc: 4460

environmental compartments Method: OECD Test Guideline 121

1,4-bis(2,3 epoxypropoxy)butane:

Distribution among : Koc: 12,59

environmental compartments Method: OECD Test Guideline 121

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

12.5 Results of PBT and vPvB assessment

Based on available data, the classification criteria are not met.

12.6 Endocrine disrupting properties

Based on available data, the classification criteria are not met.

12.7 Other adverse effects

Product:

Additional ecological

An environmental hazard cannot be excluded in the event of

information

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Assessment : Not persistent, mobile, and toxic (PMT).

Not very persistent and very mobile (vPvM).

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-

[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-

ylmethoxy)benzyl]phenoxy}methyl)oxirane:

Assessment : Not persistent, mobile, and toxic (PMT).

Not very persistent and very mobile (vPvM).

1,4-bis(2,3 epoxypropoxy)butane:

Assessment : Not persistent, mobile, and toxic (PMT).

Not very persistent and very mobile (vPvM).

Reaction mass of bis(2,3-epoxypropyl) terephthalate and tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate:

Assessment : Not persistent, mobile, and toxic (PMT).

Not very persistent and very mobile (vPvM).

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 3082
ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 9
ADR : 9
RID : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADN

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9

EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction : 964

(passenger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV)

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

: This product does not contain substances of very high concern.

 Conditions of restriction for the following entries should be considered:
 Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please

contact your vendor.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

ENVIRONMENTAL HAZARDS

Water hazard class : WGK 2 obviously hazardous to water

(Germany) Classification according to AwSV, Annex 1 (5.2)

Other regulations:

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

E2

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed. H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled. H360F : May damage fertility.

H361f : Suspected of damaging fertility.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

H373 : May cause damage to organs through prolonged or repeated

exposure if swallowed.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE DFG MAK / MAK : MAK value

DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

Further information

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method
Eye Dam. 1 H318 Calculation method
Skin Sens. 1 H317 Calculation method
Repr. 1B H360F Calculation method
Aquatic Chronic 2 H411 Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

according to Regulation (EC) No. 1907/2006, as amended



ARALDITE® 2014-2 RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.06.2024

 2.0
 21.08.2025
 400001015910
 Date of first issue: 03.06.2016

Print Date 10.10.2025

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.