

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Yachtcare Gelcoat Spachtel VT weiss

Version	Revision Date:	Date of last issue: 03.02.2021
2.1 GB / EN	27.05.2021	Date of first issue: 05.09.2019

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Yachtcare Gelcoat Spachtel VT weiss  
Product code : 155.653

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Body filler/stopper  
Recommended restrictions : public use, professional use, Industrial use  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH  
Esinger Steinweg 50  
25436 Uetersen  
Germany  
info@vosschemie.de  
Telephone : 04122 717 0  
Telefax : 04122 717158  
**Responsible Department** : Laboratory  
04122 717 0  
sds@vosschemie.de

#### 1.4 Emergency telephone number

Telephone : Giftinformationszentrum (GIZ)-Nord,  
Göttingen, Deutschland  
0551 19240

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version  
2.1

GB / EN

Revision Date:  
27.05.2021

Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements :  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :  
P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

##### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

##### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.

##### Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version  
2.1

GB / EN

Revision Date:  
27.05.2021

Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

### Additional Labelling

**EUH208** Contains Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-. May produce an allergic reaction.

**EUH211** Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture  
contains  
Resin

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
vinyltoluene	25013-15-4 246-562-2 01-2119622074-50, 01-2120106403-73	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
Titanium dioxide	13463-67-7 236-675-5 01-2119489379-17	Carc. 2; H351	>= 10 - < 20
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	Not Assigned 911-490-9 01-2119979579-10	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 0.1 - < 0.25
Substances with a workplace exposure limit :			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Yachtcare Gelcoat Spachtel VT weiss

Version 2.1 GB / EN Revision Date: 27.05.2021 Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

Talc	14807-96-6 238-877-9		>= 30 - < 50
------	-------------------------	--	--------------

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
Move out of dangerous area.  
Take off contaminated clothing and shoes immediately.  
Do not leave the victim unattended.  
Symptoms of poisoning may appear several hours later.  
Show this safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
If easy to do, remove contact lens, if worn.  
Consult a physician.
- If swallowed : Do NOT induce vomiting.  
Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
Causes serious eye irritation.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.  
Keep under medical supervision for at least 48 hours.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version	Revision Date:	Date of last issue: 03.02.2021
2.1	27.05.2021	Date of first issue: 05.09.2019

Water spray jet  
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Do not smoke.  
Avoid contact with skin, eyes and clothing.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.  
Do not flush with water.

### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Yachtcare Gelcoat Spachtel VT weiss

Version  
2.1

GB / EN

Revision Date:  
27.05.2021

Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Wear personal protective equipment.  
Avoid contact with skin and eyes.  
Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture.  
Avoid inhalation of dust from sanding.

Advice on protection against fire and explosion : Vapours may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Keep away from direct sunlight.

Advice on common storage : Incompatible with oxidizing agents.  
Keep away from food and drink.

#### 7.3 Specific end use(s)

Specific use(s) : No data available

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	TWA (Respirable dust)	1 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	0.1 mg/m <sup>3</sup>	2004/37/EC
Further information: Carcinogens or mutagens				
Titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40
Barium sulphate	7727-43-7	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
		TWA (Respirable dust)	4 mg/m <sup>3</sup>	GB EH40

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version  
2.1

GB / EN

Revision Date:  
27.05.2021

Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	Workers	Inhalation	Long-term systemic effects	9.8 mg/m3
	Workers	Skin contact	Long-term systemic effects	1.4 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2.9 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	0.83 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	Fresh water	0.048 mg/l
	Marine water	0.005 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	1.2 mg/kg
	Marine sediment	0.12 mg/kg
	Soil	0.21 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

#### Hand protection

Material : Fluorinated rubber  
Break through time : > 480 min  
Glove thickness : >= 0.4 mm  
Directive : DIN EN 374  
Protective index : Class 6

Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : >= 0.4 mm  
Directive : DIN EN 374  
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version	Revision Date:	Date of last issue: 03.02.2021
2.1	27.05.2021	Date of first issue: 05.09.2019

- choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection Butyl gloves are not suitable. Avoid natural rubber gloves.
- Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing
- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.  
Dry sanding, flame cutting and/or welding of the cured material will give rise to dust and/or hazardous fumes.  
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
- Filter type : Combined particulates and organic vapour type (A-P)
- Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
Avoid contact with the skin and the eyes.  
Use only with adequate ventilation.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

- Physical state : paste
- Colour : white
- Odour : aromatic
- Melting point/freezing point : -76.8 °C  
Literature value vinyltoluene
- Boiling point/boiling range : 168 °C  
Literature value vinyltoluene
- Upper explosion limit / Upper flammability limit : 6.1 %(V)  
Literature value vinyltoluene
- Lower explosion limit / Lower flammability limit : 1.9 %(V)  
Literature value vinyltoluene
- Flash point : 53 °C  
Literature value vinyltoluene
- Ignition temperature : 575 °C  
Literature value vinyltoluene



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Yachtcare Gelcoat Spachtel VT weiss

Version	Revision Date:	Date of last issue: 03.02.2021
2.1	27.05.2021	Date of first issue: 05.09.2019

pH : Not applicable substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-  
octanol/water : No data available

Vapour pressure : 2 hPa (20 °C)  
Literature value vinyltoluene

Density : ca. 1.9 g/cm<sup>3</sup> (20 °C)

### 9.2 Other information

Explosives : Not explosive  
In use, may form flammable/explosive vapour-air mixture.

Self-ignition : not auto-flammable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Avoid radical-forming starting agents, peroxides and reactive metals.  
Polymerisation can occur. Polymerisation is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.

### 10.5 Incompatible materials

Materials to avoid : Strong acids and oxidizing agents  
polymerisation initiators

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version  
2.1

GB / EN

Revision Date:  
27.05.2021

Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

#### Components:

##### **vinyltoluene:**

Acute oral toxicity : LD50 Oral (Rat): 3,680 mg/kg  
Acute inhalation toxicity : LC50: 16.861 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Acute dermal toxicity : LD50 Dermal (Rabbit): 4,490 mg/kg

##### **Titanium dioxide:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LD50 (Rat): > 6.8 mg/l  
Exposure time: 4 h

##### **Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:**

Acute oral toxicity : LD50 Oral (Rat): 619 mg/kg  
Method: OECD Test Guideline 401  
Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402

#### **Talc:**

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

#### **Skin corrosion/irritation**

Causes skin irritation.

#### Components:

##### **vinyltoluene:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version 2.1 GB / EN Revision Date: 27.05.2021 Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

---

Assessment : Irritating to skin.  
Result : Skin irritation

### Titanium dioxide:

Remarks : No skin irritation

### Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Result : Skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### vinyltoluene:

Assessment : Irritating to eyes.  
Result : Moderate eye irritation

### Titanium dioxide:

Remarks : Dust contact with the eyes can lead to mechanical irritation.

### Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Result : Irreversible effects on the eye

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Components:

#### Titanium dioxide:

Remarks : No known sensitising effect.

### Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Test Type : Local lymph node assay (LLNA)  
Species : Mouse  
Assessment : The product is a skin sensitiser, sub-category 1B.  
Method : OECD Test Guideline 429  
Result : positive

### Germ cell mutagenicity

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Yachtcare Gelcoat Spachtel VT weiss

Version  
2.1

GB / EN

Revision Date:  
27.05.2021

Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

---

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

Not classified based on available information.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **vinyltoluene:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

#### **vinyltoluene:**

Toxicity to fish : LC50 (Fat head minnow): 5.2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.3 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 2.6 mg/l  
Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 1.6 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 1.16 mg/l  
Exposure time: 30 d

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version 2.1 GB / EN Revision Date: 27.05.2021 Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

---

Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.32 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### Titanium dioxide:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h

### Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 48 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): > 1,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

## 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

### Components:

#### vinyltoluene:

Bioaccumulation : Species: Fish  
Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 3.58

### Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-:

Partition coefficient: n-octanol/water : log Pow: 2.17 (20 °C)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Yachtcare Gelcoat Spachtel VT weiss

Version 2.1 GB / EN Revision Date: 27.05.2021 Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

---

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Dispose of in accordance with local regulations.  
Dispose of wastes in an approved waste disposal facility.  
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Store containers and offer for recycling of material when in accordance with the local regulations.  
Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:  
07 02 08, other still bottoms and reaction residues

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Yachtcare Gelcoat Spachtel VT weiss

Version  
2.1

GB / EN

Revision Date:  
27.05.2021

Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADN** : UN 1866  
**ADR** : UN 1866  
**RID** : UN 1866  
**IMDG** : UN 1866  
**IATA** : UN 1866

#### 14.2 UN proper shipping name

**ADN** : RESIN SOLUTION  
**ADR** : RESIN SOLUTION  
**RID** : RESIN SOLUTION  
**IMDG** : RESIN SOLUTION  
**IATA** : Resin solution

#### 14.3 Transport hazard class(es)

**ADN** : 3  
**ADR** : 3  
**RID** : 3  
**IMDG** : 3  
**IATA** : 3

#### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version 2.1 GB / EN Revision Date: 27.05.2021 Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

---

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Class 3 - Flammable liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Class 3 - Flammable liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version  
2.1

GB / EN

Revision Date:  
27.05.2021

Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: < 250 g/l  
VOC content for the product in a ready to use condition.

### 15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

## SECTION 16: Other information

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H351 : Suspected of causing cancer if inhaled.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
2004/37/EC / TWA : Long term exposure limit  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Yachtcare Gelcoat Spachtel VT weiss

Version  
2.1

GB / EN

Revision Date:  
27.05.2021

Date of last issue: 03.02.2021  
Date of first issue: 05.09.2019

Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.