

### SAFETY DATA SHEET

## Eco-Laminate

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

##### Trade name

Eco-Laminate

##### Product no.

PR03

##### Unique formula identifier (UFI)

FYG0-W0RF-S00R-QP4N

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture

Binder

##### Product code (A.I.S.E.)

AISE-P1008 / Coating product (Paint, Filler, Putty, Thinner). Semi-Automatic process.

##### Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 12	Manufacture of plastics products, including compounding and conversion
SU 19	Building and construction work
Product category	Description
PC 32	Polymer Preparations and Compounds
PC-TEC-27	Products for the polymerisation of resins and foams (includes curing agents, hardeners, cross-linkers)
Process category	Description
PROC 10	Roller application or brushing
PROC 19	Hand-mixing with intimate contact and only PPE available
Article category	Description
AC 13	Plastic articles
Environmental release category	Description
ERC 1	Manufacture of substances
ERC 5	Industrial use resulting in inclusion into or onto a matrix
ERC 8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
ERC 8f	Wide dispersive outdoor use resulting in inclusion into or onto a matrix

##### Uses advised against

None known.

#### 1.3. Details of the supplier of the safety data sheet

##### Company and address

Polyestershopp BV

Oostbaan 680  
2841 ML Moordrecht  
Netherlands  
+31 85 0220090

#### Contact person

-

#### E-mail

info@polyestershoppen.nl

#### Revision

16/04/2025

#### SDS Version

1.0

### 1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H335, May cause respiratory irritation.

Repr. 2; H361, Suspected of damaging fertility or the unborn child.

STOT RE 1; H372, Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

#### Hazard pictogram(s)



#### Signal word

Danger

#### Hazard statement(s)

Flammable liquid and vapour. (H226)

May be fatal if swallowed and enters airways. (H304)

Causes skin irritation. (H315)

Causes serious eye irritation. (H319)

May cause respiratory irritation. (H335)

Suspected of damaging fertility or the unborn child. (H361)

Causes damage to organs through prolonged or repeated exposure. (H372)

Harmful to aquatic life with long lasting effects. (H412)

#### Precautionary statement(s)

##### General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

##### Prevention

Do not breathe vapour/mist. (P260)

Do not eat, drink or smoke when using this product. (P270)

### Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)

Get medical advice/attention if you feel unwell. (P314)

### Storage

Store locked up. (P405)

### Disposal

Dispose of contents/container in accordance with local regulation (P501)

### Hazardous substances

styrene

### Additional labelling

EUH208, Contains Cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

UFI: FYG0-W0RF-S00R-QP4N

## 2.3. Other hazards

### Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.  
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
styrene	CAS No.: 100-42-5 EC No.: 202-851-5 UK-REACH: Index No.: 601-026-00-0	25-40%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Repr. 2, H361 STOT RE 1, H372 Aquatic Chronic 3, H412	
Cobalt bis(2-ethylhexanoate)	CAS No.: 136-52-7 EC No.: 205-250-6 UK-REACH: Index No.:	<0.1%	Skin Sens. 1A, H317 Eye Irrit. 2, H319 Repr. 1B, H360 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 3, H412	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

### Other information

-

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

### Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

### Information to medics

Bring this safety data sheet or the label from this product.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

#### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

The product should be tested for peroxide formation or discarded after 6 months.

Avoid direct contact with the product.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.

2. Material appears to be discolored.

3. Deterioration or distortion of storage container.

4. Thermal shock (sunlight).

5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

##### Recommended storage material

Keep only in original packaging.

##### Storage conditions

Dry, cool and well ventilated

##### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

styrene

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 430

Short term exposure limit (15 minutes) (ppm): 250

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 1080

Cobalt bis(2-ethylhexanoate)

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 0,1 (as Co)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

### DNEL

Cobalt bis(2-ethylhexanoate)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	37 µg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	235.1 µg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	175 µg/kg bw/day

styrene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	343 mg/kg/day
Long term – Systemic effects - General population	Dermal	343 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	406 mg/kg/day
Long term – Systemic effects - Workers	Dermal	406 mg/kg bw/day
Long term – Local effects - General population	Inhalation	1 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	10,2 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	1 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	85 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	85 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	182,75 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	10 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	306 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	174,25 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	10 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	289 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	2,1 mg/kg/day
Long term – Systemic effects - General population	Oral	7.7 µg/kg bw/day

### PNEC

Cobalt bis(2-ethylhexanoate)

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1.06 µg/L
Freshwater sediment		53.8 mg/kg
Marine water		2.36 µg/L
Marine water sediment		69.8 mg/kg
Sewage treatment plant		370 µg/L
Soil		10.9 mg/kg
styrene		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0,028 mg/L
Freshwater		28-40 µg/L
Freshwater sediment	Single	0,614 mg/kg
Freshwater sediment		418-614 µg/kg
Intermittent release	Single	0,04 mg/L
Intermittent release (freshwater)		40 µg/L
Marine water	Single	0,014 mg/L
Marine water		14-40 µg/L
Marine water sediment	Single	0,307 mg/kg
Marine water sediment		307-418 µg/kg
Sewage treatment plant	Single	5 mg/L
Sewage treatment plant		5 mg/L
Soil	Single	0,2 mg/kg
Soil		146-200 µg/kg

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Do not recirculate outlet air that contain the substances.

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

Take off contaminated clothing and wash it before reuse.

### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

## Individual protection measures, such as personal protective equipment

### Generally

Use only UKCA marked protective equipment.

### Respiratory Equipment

Work situation	Type	Class	Colour	Standards
In case of inadequate ventilation	A	Class 1 (low capacity)	Brown	EN14387



### Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn.	-	-



### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,2	> 240	EN374-2, EN16523-1, EN388



### Eye protection

Type	Standards
Safety glasses with side shields.	EN166



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Blue

#### Odour / Odour threshold

Characteristic (Odour threshold: 0,15-25 ppm)

#### pH

-

#### pH in solution

7 (0,02%)

#### Density (g/cm<sup>3</sup>)

1.2 (23 °C)

#### Kinematic viscosity

>20.5 mm<sup>2</sup>/s (40 °C)

#### Dynamic viscosity

225 mPa.s (23 °C)

#### Particle characteristics

Does not apply to liquids.

### Phase changes

#### Melting point/Freezing point (°C)

<25

#### Softening point/range (°C)

Does not apply to liquids.



### Boiling point (°C)

145

### Vapour pressure

1.7 kPa

### Relative vapour density

3.6

### Decomposition temperature (°C)

No data available.

## Data on fire and explosion hazards

### Flash point (°C)

33

### Flammability (°C)

The material is ignitable.

### Auto-ignition temperature (°C)

490

### Lower and upper explosion limit (% v/v)

1.1 - 6.1

## Solubility

### Solubility in water

Insoluble

### n-octanol/water coefficient (LogKow)

No data available.

### Solubility in fat (g/L)

No data available.

## 9.2. Other information

### Evaporation rate (n-butylacetate = 100)

1240

### Other physical and chemical parameters

No data available.

### Oxidizing properties

No data available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly reactive and can auto-polymerize as a result of internal peroxide accumulation. The peroxides formed in these reactions are extremely shock- and heat-sensitive.

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/substance	styrene
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/kg bw

Product/substance	styrene
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg bw

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

#### STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

### 11.2. Information on other hazards

#### Long term effects

Reproductive toxicity: This product contains teratogenic substances, which may produce anomalies and/or developmental defects to the human offspring. Adverse effects include: death, growth retardation, congenital disorders, delayed mental development, and functional disorders. This product contains reprotoxic substances, which may harm the reproductive capacity. Adverse effects include: sterility, effects on the sexual function, lowered effective fertility and dysfunctional menstrual cycle.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

#### Other information

styrene has been classified by IARC as a group 2A carcinogen.

Cobalt bis(2-ethylhexanoate) has been classified by IARC as a group 2B carcinogen.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Product/substance	styrene
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	3,24 - 4,99 mg/L

Product/substance	styrene
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	4,7 mg/L

Product/substance	styrene
Species:	Daphnia
Duration:	21 days
Test:	NOEC
Result:	1,01 mg/L

Product/substance	styrene
Species:	Daphnia
Duration:	96 hours
Test:	LC50
Result:	9,5 mg/L

Product/substance	styrene
Species:	Algae
Duration:	96 hours
Test:	EC50
Result:	6,3 mg/L

Harmful to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

#### 12.3. Bioaccumulative potential

Product/substance	styrene
LogKow:	2.95
Conclusion:	-

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

#### 12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

#### 12.7. Other adverse effects

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 6 - Acute toxicity

HP 10 - Toxic for reproduction

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

**EWC code**




08 01 11\*

Waste paint and varnish containing organic solvents or other dangerous substances

**Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

### SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1866	RESIN SOLUTION	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information .
IMDG	UN1866	RESIN SOLUTION	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information .
IATA	UN1866	RESIN SOLUTION	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	See below for additional information .

\* Packing group

\*\* Environmental hazards

**Additional information**

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with

transport.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

##### Demands for specific education

No specific requirements.

##### SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

##### REACH, Annex XVII

styrene is subject to UK-REACH restrictions (entry 40).

##### Additional information

Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

##### Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H360, May damage fertility or the unborn child.

H361, Suspected of damaging fertility or the unborn child.

H372, Causes damage to organs through prolonged or repeated exposure.

H400, Very toxic to aquatic life.

H412, Harmful to aquatic life with long lasting effects.

#### The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)

LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU 12 = Manufacture of plastics products, including compounding and conversion

SU 19 = Building and construction work

PROC 10 = Roller application or brushing  
PROC 19 = Hand-mixing with intimate contact and only PPE available  
PC 32 = Polymer Preparations and Compounds  
PC-TEC-27 = Products for the polymerisation of resins and foams (includes curing agents, hardeners, cross-linkers)  
AC 13 = Plastic articles  
ERC 1 = Manufacture of substances  
ERC 5 = Industrial use resulting in inclusion into or onto a matrix  
ERC 8c = Wide dispersive indoor use resulting in inclusion into or onto a matrix  
ERC 8f = Wide dispersive outdoor use resulting in inclusion into or onto a matrix

### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

### Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.  
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.  
The classification of the mixture in regard to physical hazards has been based on experimental data.

### The safety data sheet is validated by

H.A.B.

### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a

triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en