SAFETY DATA SHEET

RESION EP-MONOTint, EP-PastelTint

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

RESION EP-MONOTint, EP-PastelTint

Product no.

EP901, EP903

Unique formula identifier (UFI)

3A50-5057-T00D-QAVN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Filler

Use descriptors (REACH)

Sectors of use	**Description**
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 12	Manufacture of plastics products, including compounding and conversion
SU 19	Building and construction work
Product category	**Description**
PC 32	Polymer Preparations and Compounds
Process category	**Description**
PROC 19	Hand-mixing with intimate contact and only PPE available
PROC 2	Use in closed, continuous PROC ess with occasional controlled exposure
PROC 5	Mixing or blending in batch PROC esses for formulation of preparations and articles (multistage and/or significant contact)
Article category	**Description**
AC 13	Plastic articles
Environmental release category	**Description**
ERC 3	Formulation in materials
ERC 5	Industrial use resulting in inclusion into or onto a matrix
ERC 8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
ERC 8f	Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Polyestershoppen BV
Oostbaan 680
2841 ML Moordrecht
Netherlands
+31 85 0220090

Contact person

-

E-mail

info@polyestershoppen.nl

▼Revision

28/09/2026

▼SDS Version

5.0

▼Date of previous version

09/12/2025 (4.0)

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 111 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. ▼Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.
Skin Sens. 1; H317, May cause an allergic skin reaction.
Eye Irrit. 2; H319, Causes serious eye irritation.
Repr. 1B; H360F, May damage fertility.
Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. ▼Label elements

▼Hazard pictogram(s)

▼Signal word

Danger

▼Hazard statement(s)

Causes skin irritation. (H315)
May cause an allergic skin reaction. (H317)
Causes serious eye irritation. (H319)
May damage fertility. (H360F)
Toxic to aquatic life with long lasting effects. (H411)

▼Precautionary statement(s)

General
If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

▼Prevention
Avoid breathing mist/vapour. (P261)
Wear eye protection/protective gloves/protective clothing. (P280)

▼Response
IF exposed or concerned: Get medical advice/attention. (P308+P313)
If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)

▼Storage
Store locked up. (P405)

Disposal
Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances
bis-[4-(2,3-epoxipropoxi)phenyl]propane
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

▼Additional labelling
EUH205, Contains epoxy constituents. May produce an allergic reaction.
EUH211, Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Restricted to professional users.

UFI: 3A50-5057-T00D-QAVN

2.3. Other hazards

Additional warnings
Contains epoxy constituents. May produce an allergic reaction.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable. This product is a mixture.

3.2. ▼Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
bis-[4-(2,3-epoxipropoxi)phenyl]propane	CAS No.: 1675-54-3 EC No.: 216-823-5 UK-REACH: Index No.: 603-073-00-2	25-40%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Aquatic Chronic 2, H411	
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	CAS No.: 933999-84-9 EC No.: 618-939-5 UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Repr. 1B, H360F	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	CAS No.: 9003-36-5 EC No.: 500-006-8 UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

▼Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.
In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.
Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. ▼Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Health Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. ▼Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
Avoid direct contact with the product.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼Conditions for safe storage, including any incompatibilities

Store locked up. A sign warning of toxic materials shall be affixed the room and cupboard containing the product(s).
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage conditions

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼DNEL

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	0.0893 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	0.75 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	0.87 mg/m3
Long term – Systemic effects - Workers	Inhalation	4.93 mg/m3
Short term – Systemic effects - General population	Oral	0.5 mg/kg bw/day

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62.5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	104.15 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	8.7 mg/m3
Long term – Systemic effects - Workers	Inhalation	29.39 mg/m3
Long term – Systemic effects - General population	Oral	6.25 mg/kg bw/day

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	13.6 µg/cm²
Long term – Local effects - Workers	Dermal	22.6 µg/cm²
Long term – Systemic effects - General population	Dermal	1.1 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	2.2 mg/kg bw/day
Short term – Local effects - General population	Dermal	13.6 µg/cm²
Short term – Local effects - Workers	Dermal	22.6 µg/cm²
Long term – Local effects - General population	Inhalation	0.27 mg/m³
Long term – Local effects - Workers	Inhalation	0.44 mg/m³
Long term – Systemic effects - General population	Inhalation	1.94 mg/m³
Long term – Systemic effects - Workers	Inhalation	3.88 mg/m³
Short term – Systemic effects - General population	Inhalation	1.94 mg/m³
Short term – Systemic effects - Workers	Inhalation	3.88 mg/m³
Long term – Systemic effects - General population	Oral	0.55 mg/kg bw/day
Short term – Systemic effects - General population	Oral	0.55 mg/kg bw/day

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Duration:	Route of exposure:	DNEL:

Long term – Local effects - General population	Inhalation	28 µg/m³
Long term – Local effects - Workers	Inhalation	170 µg/m³

▼PNEC

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater	Single	0.006 mg/L
Freshwater sediment	Single	0.341 mg/kg
Marine water	Single	0.001 mg/L
Marine water sediment	Single	0.034 mg/kg
Sewage treatment plant	Single	10 mg/L
Soil	Single	0.065 mg/kg

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater	Single	0.003 mg/L
Freshwater sediment		0.294 mg/kg
Intermittent release	Single	0.025 mg/L
Marine water	Single	0 mg/L
Marine water sediment	Single	0.029 mg/kg
Sewage treatment plant	Single	10 mg/L
Soil	Single	0.237 mg/kg

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		0.111 mg/L
Freshwater sediment		2.29 mg/kg
Intermittent release (freshwater)		0.111 mg/L
Marine water		0.011 mg/L
Marine water sediment		0.229 mg/kg
Sewage treatment plant		1 mg/L
Soil		1.8 mg/kg

8.2. ▼Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼Appropriate technical measures

Do not recirculate outlet air that contain the substances.
The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and

emergency showers are clearly marked.
Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures
Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure
Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally
Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
No special when used as intended.			

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,2	> 240	EN374-2, EN16523-1, EN388	

▼Eye protection

Type	Standards	
Safety glasses with side shields.	EN 166 / EN ISO 16321-1	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state
Paste

Colour
Various colours

Odour / Odour threshold
Characteristic

pH
No data available.

Density (g/cm^3)
1.766

Kinematic viscosity

No data available.

Particle characteristics
No data available.

Phase changes

Melting point/Freezing point (°C)
No data available.

Softening point/range (°C)
No data available.

Boiling point (°C)
No data available.

Vapour pressure
No data available.

Relative vapour density
No data available.

Decomposition temperature (°C)
No data available.

Data on fire and explosion hazards

Flash point (°C)
>150

Flammability (°C)
No data available.

Auto-ignition temperature (°C)
No data available.

Lower and upper explosion limit (% v/v)
No data available.

Solubility

Solubility in water
No data available.

n-octanol/water coefficient (LogKow)
No data available.

Solubility in fat (g/L)
No data available.

9.2. Other information

Other physical and chemical parameters
No data available.

Oxidizing properties
No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available.

10.2. Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions
None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼Acute toxicity

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Test method:	OECD 401
Species:	Rat, male/female
Route of exposure:	Oral
Test:	LD50
Result:	>2000 mg/kg bw

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Test method:	OECD 403
Species:	Rat, male
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	>5.09 mg/L

Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	15000 mg/kg

Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	23000 mg/kg

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Test method:	OECD 404
Species:	Rabbit
Duration:	4 hours
Result:	No adverse effect observed (Not irritating)

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

▼Respiratory sensitization

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Test method:	OECD 429

Species: Mouse, female
Result: No adverse effect observed (not sensitising)

Based on available data, the classification criteria are not met.

Skin sensitisation

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Test method: OECD 429
Species: Mouse, female
Result: No adverse effect observed (not sensitising)

May cause an allergic skin reaction.

▼Germ cell mutagenicity

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Test method: OECD 473
Species: Mouse, Chinese Hamster Ovary (CHO)
Conclusion: No adverse effect observed

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Test method: OECD 471
Species: Bacteria, S. typhimurium
Conclusion: No adverse effect observed

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Test method: OECD 474
Species: Mouse, male/female
Conclusion: No adverse effect observed

Based on available data, the classification criteria are not met.

▼Carcinogenicity

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Test method: OESO 453
Species: Rat, male/female
Route of exposure: Inhalation
Target organ: Lung
Duration: 24 months
Test: NOAEC
Result: 5 mg/m³
Conclusion: No adverse effect observed

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Species: Rat, male/female
Route of exposure: Oral
Duration: 24 months
Test: NOAEL
Result: 50000 ppm
Conclusion: No adverse effect observed

Based on available data, the classification criteria are not met.

▼Reproductive toxicity

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
Test method: OECD 414

Species:	Rat
Duration:	14 days
Test:	NOAEL
Result:	1000 mg/kg bw/day
Conclusion:	No adverse effect observed

May damage fertility.

▼STOT-single exposure

Based on available data, the classification criteria are not met.

▼STOT-repeated exposure

Based on available data, the classification criteria are not met.

▼Aspiration hazard

Based on available data, the classification criteria are not met.

▼Symptoms related to the physical, chemical and toxicological characteristics

Reproductive toxicity: This product contains reprotoxic substances, which may harm the reproductive capacity. Adverse effects include: sterility, effects on the sexual function, lowered effective fertility and dysfunctional menstrual cycle.
Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

11.2. Information on other hazards

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] has been classified by IARC as a group 2B.
bis-[4-(2,3-epoxipropoxi)phenyl]propane has been classified by IARC as a group 3.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Species:	Fish
Compartment:	Freshwater
Test:	LC50
Result:	>1000 mg/L

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Species:	Crustacean
Compartment:	Freshwater
Test:	EC50
Result:	>1000 mg/L

Product/substance
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Test method:	OECD 201
Species:	Algae, Pseudokirchneriella subcapitata
Compartment:	Freshwater
Duration:	72 hours
Test:	EC50
Result:	>100 mg/L

Product/substance	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	
Test method:	OECD 201
Species:	Algae, Pseudokirchneriella subcapitata
Compartment:	Freshwater
Duration:	72 hours
Test:	NOEC
Result:	>100 mg/L

Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	2 mg/L

Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	1.8 mg/L

Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	11 mg/L

Toxic to aquatic life with long lasting effects.

12.2. ▼Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. ▼Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. ▼Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)
HP 4 - Irritant (skin irritation and eye damage)
HP 10 – Toxic for reproduction
HP 13 – Sensitising
HP 14 – Ecotoxic
Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

08
WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID ***	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/ADN/RID	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	Limited quantities: 5 L Tunnel restriction code: (-) See below for additional information.
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	Limited quantities: 5 L EmS: F-A S-F See below for additional information.
IATA	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	See below for additional information.

* Packing group
** Environmental hazards
*** UN number or ID number

Additional information

This product is within scope of the regulations of transport of dangerous goods.
These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR/ADN/RID/IMDG/IATA provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (ADR, IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).
-

ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user
Not applicable.

14.7. Maritime transport in bulk according to IMO instruments
No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

▼Restrictions for application
Restricted to professional users.
The product must not be used professionally by persons under 18 years of age.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education
Use of this product requires dedicated training in work with polyurethane and epoxy products.

SEVESO - Categories / dangerous substances
E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

Additional information
Not applicable.

▼Sources
The Management of Health and Safety at Work Regulations 1999.
The Health and Safety at Work etc. Act 1974 Regulations 2013.
Control of Major Accident Hazards (COMAH) Regulations 2015.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment
No

SECTION 16: Other information

▼Full text of H-phrases as mentioned in section 3
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H360F, May damage fertility.
H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1
LCS "C" = Consumer uses: Private households (= general public = consumers)
LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites
LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 12 = Manufacture of plastics products, including compounding and conversion

SU 19 = Building and construction work
PROC 19 = Hand-mixing with intimate contact and only PPE available
PROC 2 = Use in closed, continuous PROC ess with occasional controlled exposure
PROC 5 = Mixing or blending in batch PROC esses for formulation of preparations and articles (multistage and/or significant contact)
PC 32 = Polymer Preparations and Compounds
AC 13 = Plastic articles
ERC 3 = Formulation in materials
ERC 5 = Industrial use resulting in inclusion into or onto a matrix
ERC 8c = Wide dispersive indoor use resulting in inclusion into or onto a matrix
ERC 8f = Wide dispersive outdoor use resulting in inclusion into or onto a matrix

▼Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EC = Effective concentration
ED = Effective dose
EINECS = European Inventory of Existing Commercial chemical Substances
EL = Effective Loading
ErC = Concentration associated with x% growth rate response
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
HP = Hazardous Property code
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IC = X maximum inhibitory concentration
IMDG = International Maritime Dangerous Goods
LC = Lethal concentration
LCLo = Value is the lowest concentration of a material in air reported to have caused the death of animals or humans
LD = Lethal dose
LOAEC = Lowest Observed Adverse Effect Concentration
LOAEL = Lowest Observed Adverse Effect Level
LOEC = Lowest Observed Effect Concentration
LogKow = logarithm of the n-octanol/water coefficient
LL = Lethal Loading
M = For multiplication factor
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NOAEC = No Observed Adverse Effect Concentration
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration

NOELR = No Observable Effect Loading Rate
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The safety data sheet is validated by

H.A.B.

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-en