## SAFETY DATA SHEET

# **RESION Floor Finishcoat Matt Hardener**

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

### Trade name

**RESION Floor Finishcoat Matt Hardener** 

Product no.

FS811

Unique formula identifier (UFI)

FCD0-N0RS-W00Y-XANX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

**Paint** 

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

## Company and address

## Polyestershoppen BV

Oostbaan 680 2841 ML Moordrecht Netherlands +31 85 0220090

### Contact person

-

## E-mail

info@polyestershoppen.nl

## Revision

16/08/2024

# **SDS Version**

3.0

# Date of previous version

13/12/2023 (2.0)

## 1.4. ▼Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

## **SECTION 2: Hazards identification**

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

### 2.1. Classification of the substance or mixture

Skin Sens. 1; H317, May cause an allergic skin reaction.



Acute Tox. 4; H332, Harmful if inhaled. STOT SE 3; H335, May cause respiratory irritation. Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

### Hazard pictogram(s)



# Signal word

Warning

## Hazard statement(s)

May cause an allergic skin reaction. (H317) Harmful if inhaled. (H332) May cause respiratory irritation. (H335) Harmful to aquatic life with long lasting effects. (H412)

### Precautionary statement(s)

### General

If medical advice is needed, have product container or label at hand. (P101) Keep out of reach of children. (P102)

#### Prevention

Wear eye protection/protective gloves/protective clothing. (P280) Avoid breathing mist/vapour. (P261)

#### Response

If skin irritation or rash occurs: Get medical advice/attention. (P333+P313) IF ON SKIN: Wash with plenty of water and soap. (P302+P352)

### Storage

Store locked up. (P405)

### Disposal

Dispose of contents/container in accordance with local regulation (P501)

### Hazardous substances

Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)

Hexamethylene diisocyanate, oligomers

HDI oligomers, isocyanurate

HDI oligomers, iminooxadiazindione

Cyclohexyldimethylamine

hexamethylene-di-isocyanate

## ▼Additional labelling

Contains isocyanates. May produce an allergic reaction. Adequate training is required before industrial or professional use.

UFI: FCD0-N0RS-W00Y-XANX

## 2.3. Other hazards

## Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

# SECTION 3: Composition/information on ingredients

## 3.1. Substances

Not applicable. This product is a mixture.

## 3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
ri ouuct/ substance	Iuciiliici3	/U VV/ VV	Ciassification	INOLE



Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)	CAS No.: 666723-27-9 EC No.: 679-494-0 UK-REACH: Index No.:	40-60%	Skin Sens. 1, H317 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Chronic 3, H412	[19]
Hexamethylene diisocyanate, oligomers	CAS No.: 28182-81-2 EC No.: 500-060-2 UK-REACH: Index No.:	25-40%	Skin Sens. 1, H317	
HDI oligomers, isocyanurate	CAS No.: 28182-81-2 EC No.: 931-274-8 UK-REACH: Index No.:	10-15%	Skin Sens. 1, H317 Acute Tox. 4, H332 STOT SE 3, H335	
HDI oligomers, iminooxadiazindione	CAS No.: EC No.: 931-297-3 UK-REACH: Index No.:	5-10%	Skin Sens. 1, H317 Acute Tox. 4, H332 STOT SE 3, H335	
Cyclohexyldimethylamine	CAS No.: 98-94-2 EC No.: 202-715-5 UK-REACH: Index No.:	<1%	Flam. Liq. 3, H226 Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 3, H331 Aquatic Chronic 2, H411	
hexamethylene-di-isocyanate	CAS No.: 822-06-0 EC No.: 212-485-8 UK-REACH: Index No.: 615-011-00-1	<0.25%	Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.50 %) Eye Irrit. 2, H319 Acute Tox. 3, H331 Resp. Sens. 1, H334 (SCL: 0.50 %) STOT SE 3, H335	[3]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

### Other information

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.

## Skin contact

IF ON SKIN: Wash with plenty of water and soap.



Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### Eve contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

### **Burns**

Not applicable.

### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation or rash occurs: Get medical advice/attention.

### Information to medics

Bring this safety data sheet or the label from this product.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

## 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO<sub>x</sub>)

Carbon oxides (CO / CO2)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

## 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

## 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.



See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

## 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### Recommended storage material

Keep only in original packaging.

### Storage conditions

Dry, cool and well ventilated

### Incompatible materials

**Bases** 

Strong acids

Strong oxidizing agents

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No substances are listed in the national list of substances with an occupational exposure limit.

### DNEL

Cyclohexyldimethylamine

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	600 μg/kgbw/day
Long term – Local effects - Workers	Inhalation	8.3 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	530 μg/m³
Short term – Local effects - Workers	Inhalation	8.3 mg/m <sup>3</sup>
hexamethylene-di-isocyanate		
Duration:	Route of exposure:	DNEL:
Long term – Local effects - Workers	Inhalation	35 μg/m³
Short term – Local effects - Workers	Inhalation	70 μg/m³

### **PNEC**

Cyclohexyldimethylamine

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3.5-12 μg/L
Freshwater sediment		36.92-2760 µg/kg
Intermittent release (freshwater)		35 μg/L
Marine water		350-1200 ng/L
Marine water sediment		3.69-276 μg/kg
Sewage treatment plant		20.6 mg/L
Soil		5.33-544 µg/kg

hexamethylene-di-isocyanate



Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		49 μg/L
Freshwater sediment		674 μg/kg
Marine water		4.9 μg/L
Marine water sediment		67.4 μg/kg
Sewage treatment plant		8.42 mg/L
Soil		523 μg/kg

### 8.2. ▼ Exposure controls

Apply general control to prevent unnecessary exposure

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

## **Exposure scenarios**

There are no exposure scenarios implemented for this product.

### **Exposure limits**

Occupational exposure limits have not been defined for the substances in this product.

### Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### **▼** Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

## Individual protection measures, such as personal protective equipment

### Generally

Use only UKCA marked protective equipment.

### Respiratory Equipment

Туре	Class	Colour	Standards	
Respiratory protection is not needed in the event of adequate ventilation	-	-	-	
A	Class 2 (medium capacity)	Brown	EN14387	6



Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	R



Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388	

## Eye protection



**Type** 

**Standards** 

Safety glasses with side EN166 shields.



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

### Physical state

Liquid

Colour

Pale yellow

### Odour / Odour threshold

None

**▼**pH

No relevant or available data due to the nature of the product.

▼ Density (g/cm³)

No relevant or available data due to the nature of the product.

▼ Kinematic viscosity

No relevant or available data due to the nature of the product.

### Particle characteristics

Does not apply to liquids.

### Phase changes

## ▼ Melting point/Freezing point (°C)

No relevant or available data due to the nature of the product.

## Softening point/range (°C)

Does not apply to liquids.

## ▼ Boiling point (°C)

No relevant or available data due to the nature of the product.

## **▼** Vapour pressure

No relevant or available data due to the nature of the product.

## ▼ Relative vapour density

No relevant or available data due to the nature of the product.

## ▼ Decomposition temperature (°C)

No relevant or available data due to the nature of the product.

## Data on fire and explosion hazards

### ▼ Flash point (°C)

No relevant or available data due to the nature of the product.

### ▼ Flammability (°C)

No relevant or available data due to the nature of the product.

## ▼ Auto-ignition temperature (°C)

No relevant or available data due to the nature of the product.

### ▼ Lower and upper explosion limit (% v/v)

No relevant or available data due to the nature of the product.

### Solubility

### ▼ Solubility in water

No relevant or available data due to the nature of the product.

## ▼ n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.



## ▼ Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

### 9.2. Other information

### Other physical and chemical parameters

No data available.

### **▼** Oxidizing properties

No relevant or available data due to the nature of the product.

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No data available.

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Bases

Strong acids

Strong oxidizing agents

## 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

### **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Acute toxicity

Product/substance Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)

Species: Rat Route of exposure: Oral

Result: >5000 mg/kg

Product/substance Hexamethylene diisocyanate, oligomers

Species: Rat Route of exposure: Oral

Result: >2000 mg/kg

Product/substance Hexamethylene diisocyanate, oligomers

Species: Rat

Route of exposure: Inhalation
Test: LD50
Result: 4500 ppmV

Product/substance HDI oligomers, isocyanurate

Species: Rat
Route of exposure: Oral
Test: LD50

Result: >2500 mg/kg

Product/substance HDI oligomers, isocyanurate

Species: Rat
Route of exposure: Dermal
Result: >2000 mg/kg



Product/substance HDI oligomers, iminooxadiazindione

Species: Rat Route of exposure: Oral LD50 Test:

Result: >2000 mg/kg

Product/substance Cyclohexyldimethylamine

Species: Rat Route of exposure: Oral

LD50 Test:

Result: 272-289 mg/kg

Product/substance Cyclohexyldimethylamine

Species: Rat Route of exposure: Dermal LD50 Test: Result: 380 mg/kg

Product/substance hexamethylene-di-isocyanate

Species: Route of exposure: Oral Test: LD50 Result: 959 mg/kg

Product/substance hexamethylene-di-isocyanate

Species: Rat Route of exposure: Dermal Test: LD50 Result: >7000 mg/kg

Product/substance hexamethylene-di-isocyanate

Species: Rat

Route of exposure: Inhalation LC50 (4 hours) Test: Result: 0.124 mg/L

Harmful if inhaled.

## Skin corrosion/irritation

Based on available data, the classification criteria are not met.

## Serious eye damage/irritation

Based on available data, the classification criteria are not met.

## Respiratory sensitisation

Based on available data, the classification criteria are not met.

### Skin sensitisation

May cause an allergic skin reaction.

## Germ cell mutagenicity

Based on available data, the classification criteria are not met.

## Carcinogenicity

Based on available data, the classification criteria are not met.

## Reproductive toxicity

Based on available data, the classification criteria are not met.

### STOT-single exposure

Product/substance Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)

Route of exposure: Inhalation

Conclusion: Adverse effect observed

Product/substance Hexamethylene diisocyanate, oligomers



Conclusion: Adverse effect observed

Product/substance HDI oligomers, isocyanurate

Route of exposure: Inhalation

Conclusion: Adverse effect observed

Product/substance HDI oligomers, iminooxadiazindione

Route of exposure: Inhalation

Conclusion: Adverse effect observed

Product/substance hexamethylene-di-isocyanate

Route of exposure: Inhalation

Conclusion: Adverse effect observed

May cause respiratory irritation.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

### **Endocrine disrupting properties**

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

### Other information

None known.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Product/substance Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)

Species: Fish
Duration: 96 hours
Test: LC50
Result: 95.2 mg/L

Product/substance Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)

Species: Crustacean, Daphnia magna

Duration: 48 hours
Test: EC50
Result: >100 mg/L

Product/substance Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI)

Species: Algae, Desmodesmus subspicatus

Test: EC50 Result: 72 mg/L

Harmful to aquatic life with long lasting effects.

### 12.2. ▼ Persistence and degradability

Product/substance HDI oligomers, isocyanurate

Conclusion: Not biodegradable

Product/substance HDI oligomers, iminooxadiazindione

Conclusion: Not biodegradable

## 12.3. ▼ Bioaccumulative potential



Based on available data, the classification criteria are not met.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

### 12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

## 12.7. Other adverse effects

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 6 - Acute toxicity

HP 13 - Sensitising

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

### EWC code

80

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS,

VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

### **SECTION 14: Transport information**

	14.1 14.2	14.3	14.4 14.5 Other
	UN / ID UN proper shipping name	Hazard class(es)	PG* Env** information:
ADR	-	-	
IMDG		-	
IATA	-	-	

<sup>\*</sup> Packing group

## Additional information

Not dangerous goods according to ADR, IATA and IMDG.

## 14.6. Special precautions for user

Not applicable.

## 14.7. Maritime transport in bulk according to IMO instruments

No data available.

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Restrictions for application

People under the age of 18 shall not be exposed to this product.

## Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

<sup>\*\*</sup> Environmental hazards



### Not applicable.

### ▼ REACH, Annex XVII

hexamethylene-di-isocyanate is subject to restrictions, UK-REACH annex XVII (entry 74). Cyclohexyldimethylamine is subject to UK-REACH restrictions (entry 40).

### Additional information

Tactile warning.

#### Sources

The Management of Health and Safety at Work Regulations 1999.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

### 15.2. Chemical safety assessment

Nο

#### **SECTION 16: Other information**

# Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.

H301, Toxic if swallowed.

H311. Toxic in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H331, Toxic if inhaled.

H332, Harmful if inhaled.

H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335, May cause respiratory irritation.

H411, Toxic to aquatic life with long lasting effects.

H412, Harmful to aquatic life with long lasting effects.

## ▼Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of



1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

## Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

## The safety data sheet is validated by

H.A.B.

### **▼** Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en